

1479 Juego para reparar roscas M14

HSS

Referencia	Unids.	Med. mm	L mm	Gr	€ / u
55607119	12 Pcs.	14 x 1,25	21	600	10
55686144*	Macho para bujías M14 x 1,25mm				6

Descripción

Macho de roscar	1	M 14x1,25 mm.
Colocador	1	N.º 17
Insertos	10	14x1,25 mm.



1480 Juego para reparar roscas

HSS



Referencia	Unidades	kg	€ / u
55605101	24	2,60	6

Descripción

Machos de roscar:	5	M 6x1-M 8x1,25-M10x1,5-M 12x1,75-M 14x1,25 mm.
Brocas:	4	6,3-8,3-10,4-12,4 mm.
Colocador:	5	Nº 9-11-13-15-17
Punzón:	5	Nº 9-11-13-15-17
Insertos:	25	M 6x1,25 mm.
	25	M 8x1,25 mm.
	25	M 10x1,5 mm.
	10	M 12x1,75 mm.
	10	M 14x1,25 mm.

Referencia	Descripción	€ / u
55686061*	Inserto 6x1 mm; L= 9 mm.	50
55686081*	Inserto 8x1,25; L= 12 mm.	50
55686101*	Inserto 10x1,50; L= 15 mm.	50
55686121*	Inserto 12x1,75; L= 18 mm.	50
55686141*	Inserto 14x1,25; L= 8,4 mm.	50
55686142*	Inserto 14x1,25; L= 12,4 mm.	50
55686143*	Inserto 14x1,25; L= 16,4 mm.	50

1481 Brocas rectificadas

HSS-G, DIN 338

Referencia	Ø mm	L mm	l mm	Gr*	€ / u
5220100	1,00	34	12	10	100
5220125	1,25	38	16	10	100
5220150	1,50	40	18	10	100
5220175	1,75	46	22	10	100
5220200	2,00	49	24	10	100
5220225	2,25	53	27	10	100
5220250	2,50	57	30	10	100
5220275	2,75	61	33	10	100
5220300	3,00	61	33	10	100
5220325	3,25	65	36	10	100
5220350	3,50	70	39	10	100
5220375	3,75	70	39	10	100
5220400	4,00	75	43	10	100
5220425	4,25	75	43	10	100
5220450	4,50	80	47	10	100
5220475	4,75	80	47	10	100
5220500	5,00	86	52	10	100
5220525	5,25	86	52	10	100
5220550	5,50	93	57	10	100
5220575	5,75	93	57	10	100
5220600	6,00	93	57	10	100
5220625	6,25	101	63	10	100
5220650	6,50	101	63	10	100
5220675	6,75	109	69	10	100
5220700	7,00	109	69	10	100
5220725	7,25	109	69	5	50
5220750	7,50	109	69	5	50
5220775	7,75	117	75	5	50
5220800	8,00	117	75	5	50
5220825	8,25	117	75	5	50
5220850	8,50	117	75	5	50
5220875	8,75	125	81	5	50
5220900	9,00	125	81	5	50

Referencia	Ø mm	L mm	l mm	Gr*	€ / u
5220925	9,25	125	81	5	50
5220950	9,50	125	81	5	50
5220975	9,75	133	87	5	50
5221000	10,00	133	87	5	50
5221025	10,25	133	87	5	50
5221050	10,50	133	87	5	50
5221075	10,75	142	94	5	50
5221100	11,00	142	94	5	50
5221125	11,25	142	94	5	50
5221150	11,50	142	94	5	50
5221175	11,75	142	94	5	50
5221200	12,00	151	101	5	50
5221225	12,25	151	101	5	50
5221250	12,50	151	101	5	50
5221275	12,75	151	101	5	50
5221300	13,00	151	101	5	50

"speedmaster"



Se suministra embalaje mínimo



Broca rectificada helicoidal de cobalto
Aplicaciones: Para taladrar acero aleado,
acero inoxidable, función R
(símbolo menor igual) 1000 N/mm²

1482 Estuche brocas rectificadas



Referencia	Unids.	Ø	Medida	Gr	€ / u
55001019	19 pcs.	1-10	0,5 HSS - CO	600	10
55001025	25 pcs.	1-13	0,5 HSS - CO	610	10
55001229	19 pcs.	1-10	0,5 HSS - G	700	10
55001220	116 pcs.	1-10	0,5 HSS - G	1,500	10